

水中ポンプ(横吸)

メーカーSC



HS2-2.4





KTV2-8





KRS2-C6N







KRS1022



C.W.L. (連続運転最低水位)



C.W.L. (連続運転最低水位)



季節・建機関係

型式	メーカー	口径 (インチ/mm)	出力 (KW)	電圧 (V)	揚程 (m)	吐出力 (m ³ /min)	重量 (kg)	外形寸法(mm)			ケーブル 長さ(m)	寸法図
								A	D	H		
HS2-2.4J	鶴見製作所	2/50	0.4	単相200	8	0.1	10.8	241	187	328	5	A
HS2-2.4S			0.4	単相100	8	0.1	11.3	241	184	328	5	A
KTV2-8		3/80	0.75	三相200	10	0.18	11.5	200	200	369	5	B
KTV2-15			1.5		15	0.2	19.5	240	240	396	8	B
KTV2-22			2.2		15	0.3	23	240	240	416	8	B
KTV2-37			3.7		18	0.5	35	285	285	510	8	B
KTV2-55		4/100	5.5		22	0.6	46.5	300	300	545	8	C
KRS-C6/A6			7.5		10	2.0	130	415	373	685	8	C
KRS2-D6/B6			11.0		15	2.0	158	434	407	744	8	C
KRS2-8S		8/200	11.0		10	4.0	174	472	403	814	8	C
KRS-815-50			15.0		15	4.0	235	481	440	949	8	C
KRS-819-50			18.5		20	3.0	385	572	530	1156	10	C
KRS-822-50			22.0		30	2.0	390	572	530	1156	10	C
KRS-1022-50		10/250	22.0		10	8.0	450	520	520	1439	10	C

【高揚程タイプ】

型式	メーカー	口径 (インチ/mm)	出力 (KW)	電圧 (V)	揚程 (m)	吐出力 (m ³ /min)	重量 (kg)	外形寸法(mm)			ケーブル 長さ(m)	寸法図
								A	D	H		
KTV2-15	鶴見製作所	2/50	1.5	三相200	15	0.2	19.5	240	240	396	8	B
KTV2-22			2.2		15	0.3	23	240	240	416	8	B
KTV2-37		3/80	3.7		18	0.5	35	285	285	510	8	B
KTV2-55			5.5		22	0.6	46.5	300	300	545	8	B
KTZ47.5		4/100	7.5		30	0.8	93	330	314	661	8	C
KTZ411			11.0		35	1.0	130	373	350	728	8	C